


UV-C Wall Ventilation

- ✓ Easy to retrofit into existing buildings
- ✓ Easy service when replacing the UV-C light source
- ✓ Compatible with existing ventilation solutions
- ✓ >95% Inactivation of the most common viruses and bacteria
- ✓ Alarm monitoring of each individual light source

UV-C negative-pressure ventilation with wall inlets and chimney exhaust system.

UV-C WV supplies fresh air via wall inlets with retrofitted infection protection, where the UV-C light source is mounted behind a specially designed air duct, which ensures that the outside air drawn into the stable receives the correct UV-C intensity, thereby achieving the calculated infection control.



SYSTEM CAPACITY & AIR EXCHANGE

Max. airflow (summer):	150 m³/h per pig (From 100 Kg)
Min. airflow (winter):	15 – 20 m³/h per pig (slaughter pigs/sows)

EXHAUST UNITS (FANS)

Type:	650/730/820/920 roof fans (high-efficiency IE3 AC-motors)
Diameter:	ID650/OD730, ID730/OD810, ID820/OD900, ID920/OD1000
Max. capacity:	12.400/16.000/20.000/25.000 m³/h
Motor efficiency:	0.75 kW to 1.1 kW per fan
Control:	Frequency control 3x230V (0-100% reg.) or ON/OFF 3x400V
Protection class:	IP 55

AIR INLETS (WALL INLET AND AIR DUCTS)

Type:	VE135-VFR/VE135-ER wall inlet
Mounting dimensions:	670 mm x 290 mm
Opening:	Automatically controlled from 0 to 300 mm (depending on actuator)
Air duct:	910 mm x 780 mm x 200 mm - 910 mm x 1000 mm x 200 mm
UV-C energy consumption:	40 W – 150 W (per air duct)

CONTROL AND AUTOMATIC REGULATION SYSTEM

Climate computer: RIKA Climate 108 with VE-BUS communication and Farmviewer*

Control options: Temperature °C (measured indoors/outdoors), Relative humidity RH*, CO₂ level*

Functions: Curve and age-controlled ventilation, Automatic summer/winter mode, Alarms in the event of a power failure or incorrect temperature, Alarm system with battery back-up for temperature-controlled emergency opening

OPERATING CONDITIONS

Measured static pressure:	-5 to -10 Pa
Relative humidity (RH):	60 – 70%
Temperature zone:	15 – 25°C (user-defined/depending on outdoor temperature)

* Optional extras

